

Tripod Heads – Specifications

Gibraltar Tripod Heads Specifications

	Product Number	
	4-62050-6	4-62926-7
Description:	Head-Relay Tilt	Head-Geared with Calibrations
Load Capacity:	330 lbs (150 kg)	200 lbs (90.9 kg)
Dimensions (Without Arm):	6.5" x 6.5" x 7" (16.5 x 16.5 x 17.8 cm)	10" x 10" x 12" (25.4 x 25.4 x 30.5 cm)
Control Arm:	Optional	0
Weight:	30 lbs (13.6 kg)	21 lbs (9.5 kg)
Mounting Type:	Spanner Nut 2.75" – 12 (6.8 cm)	Post O.D. 1.75" (4.37 cm)
Pan Movement:	360°	360°
Tilt Movement:	30° Up, 38° Down	53° Up, 67° Down
Gear Ratio:	N/A	Pan: 1:96 Tilt: 1:128
Camera Screw:	0.5"–13 Female (Center)	3/8–16
Camera Plate:	6.5" x 6.5" Fixed (16.5 x 16.5 cm)	8" x 10" Fixed (20 x 25.4 cm)
Additional Features:	Heavy Duty Lock Model Available (Model #4-64051-4)	N/A



4-62050-6




4-62926-7

Hercules Tripod Heads Specifications

	Product Number		
	4-52217-3	4-52926-9	4-52304-9
Description:	Head-Geared w/ Large Platform	Head-Geared w/ Calibrations	Head-Cam
Load Capacity:	50 lbs (22.7 kg)	30 lbs (13.6 kg)	80 lbs (36.3 kg)
Dimensions (Transport Mode):	8" x 10.5" x 11.5" (20 x 26.6 x 29.2 cm)	8" x 9.5" x 10.75" (20 x 23.7 x 26.9 cm)	11.75" x 8.25" x 5.5" (20 x 23.7 x 26.9 cm)
Control Arm:	0	0	2
Weight:	12 lbs (5.5 kg)	9 lbs (4.1 kg)	13.5 lbs (6.1 kg) w/ 2 Control Arms
Mounting Type:	Special Post 1.250 x 1.5"L (31.5"Ø x 38 mmL)	Special Post 1.250 x 1.5"L (31.5"Ø x 38 mmL)	Special Post 1.250 x 1.5"L (31.5"Ø x 38 mmL)
Pan Movement:	360°	360°	360°
Tilt Movement:	45° Up, 45° Down	45° Up, 90° Down	35° Up, 45° Down
Gear Ratio:	Pan – 1:96 Tilt – 1:129	Pan – 1:96 Tilt – 1:129	N/A
Camera Screw:	3/8-16	1/4-20	1/4-20 – 3/8-16
Camera Plate (Adjustable):	9" x 6" (22.5 x 15 cm)	4" x 4" (10 x 10 cm)	4.5" x 10" (11.25 x 39 cm)



4-52217-3



4-52926-9



4-52304-9

Samson Tripod Heads Specifications

	Product Number			
	4-72011-6B	4-72512-3	4-72612-S3	4-52816-2C
Description:	Head Friction	Head-Geared and Side Tilt	Head-Geared	Head Fluid Hydro
Load Capacity:	35 lbs (16 kg)	25 lbs (11.4 kg)	35 lbs (16 kg)	50 lbs (22.68 kg)
Dimensions (without Control Arms):	5.5 x 6.5 x 6.5" (14.1 x 16.6 x 16.6 cm)	8.5 x 6.5 x 6" (21.6 x 16.5 x 15.2 cm)	11.75 x 8.25 x 5.5" (15.2 x 16.5 x 19 cm)	6.75 x 6 x 7" (17.1 x 15.2 x 18 cm)
Control Arm:	2	0	1	2
Weight:	2.5 lbs (1.1 kg)	2.5 lbs (1.1 kg)	2 lbs (1 kg)	16.5 lbs (7.5 kg)
Mounting Type:	Sleeve I.D. 1.75" (4.4 cm)	Sleeve I.D. 1.75" (4.4 cm)	Sleeve I.D. 1.75" (4.4 cm)	Sleeve I.D. 1.75" (4.45 cm)
Pan Movement:	360°	360°	360°	360°
Tilt Movement:	45° Up, 90° Down	45° Up, 90° Down	35° Up, 90° Down	80° up, 80° down
Gear Ratio:	N/A	1:150	1:150	N/A
Camera Screw:	1/4-20	1/4-20	1/4-20	1/4-20 and 3/8-16
Camera Plate (Adjustable):	2.25" x 4.25" (5.6 x 10.6 cm) Fixed	6.25" x 8.5" (16.5 x 21.6 cm) Fixed	2.25" x 4.25" (5.6 x 10.6 cm) Fixed	2.25" x 5" (5.7 x 12.7 cm) Quick Change
Operational Camera Plate P/N 6-16004-8:	N/A	N/A	N/A	2.25" x 8" (5.7 x 20.3 cm) Quick Change




4-72011-6



4-72512-3



4-72612-S3



4-52816-2C